

PRELIMINARY

The simplicity of IEI keypads with the convenience of HID proximity

5 Different mounting options

- One-piece stand alone
- Two-piece stand alone (antenna remotely mounted)
- One-piece front end (Hub Controller or Wiegand Panel)
- Two-piece front end (Hub Controller or Wiegand Panel)
- One-piece glass mount (secure electronics, card presented through glass door or window)

DOOR•GARD™ Keypads

Door•Gard™ prox.pad™

**New
Enhanced
Capabilities**



- ✓ **Single Door Access Control System**
 - Integrated Reader and Controller
 - Compatible with all HID cards up to 37-bits
 - 2000 users in single door
 - 1000 Event audit trail
 - Proximity reader module remotes from controller for added security
- ✓ **Reader for IEI Secured Series Hub Controllers**
 - Combined Keypad and/or HID Proximity Reader
 - Networkable with Hub Controller
- ✓ **Reader for any Wiegand Controller**
 - *HID Proximity Reader and/or keypad
 - Up to 37-bit Wiegand Output for Proximity Reader
 - 26-bit Output for Keypad

*Before specifying prox.pad for card and code applications, check the instruction manual or check with IEI Technical Support for the prox.pad operating parameters.

IEI prox.pad is a stand-alone proximity reader and keypad. In addition to operating as a self-contained single door access control system, it now operates as a reader with all IEI Secured Series Hub Control products and with most 26-bit wiegand access control panels—as a proximity reader only, keypad with PIN only, or proximity and keypad (works with 2 man rule — check each access control system manufacturer's instructions to verify prox.pad's compatibility in these applications.)

Door•Gard™ prox.pad™

Features:

- HID compatible
- Reader module can remote for added security
- Indoor/outdoor/glass mount
- 2000 users (stand alone)
- 1000 event audit trail (stand alone)
- Works with all IEI Secured Series Hub products
- Wiegand panel front-end

Benefits:

- Compatible with all HID Proximity Cards up to 37-bit
- Card & Code operation in IEI Hub systems
- Works with most Wiegand access control systems as a keypad and/or proximity reader
- Perfect for single-door access control applications
- Accountability of access event at the door
- Assures security and integrity of controller

Specifications:

- **Users:** 2000 (stand-alone)
- **Inputs:** One request-to-exit
- **Operating voltage:** 12VDC
- **Current draw:** 30-100mA
- **Size:** 2.75" w x 5.26" h x 1.375" d
(6.98cm x 13.36cm x 3.49cm)
- **Relays:** 2
- **Duty Cycle:** Medium

Applications include:

- Schools
- Office Buildings
- Day Care facilities
- Health Clubs
- Hospitals
- Computer rooms/network closets
- Small Businesses

